

Mini Air Flow Meter

Mini pocket type air flow meter 8908/8918



8908



8918

- ▲ SMALL POCKET KNIFE SHAPE & COMPACT DESIGN
- ▲ MEASURES AIR VELOCITY, TEMP., WINDCHILL TEMP. AND RELATIVE HUMIDITY (8918 ONLY)
- ▲ WIND UNITS SELECTABLE: KNT (KNOT), BF (BEAUFORT), FPM (FEET PER MINUTE), MPH (MILE PER HOUR), MS (METER PER SECOND), KMH (KILOMETER PER HOUR)
- ▲ TEMP. UNITS °C/°F SELECTABLE
- ▲ DISPLAY MAX. WINDSPEED AND QUICK RESPONSE
- ▲ DISPLAY 5, 10, 13 SECONDS AVERAGE WINDSPEED
- ▲ WATER RESISTANT & SHOCK PROOF. 8908: IP65, 8918: IP54
- ▲ EASY TO OPERATE BY ONLY TWO BUTTONS
- ▲ HOLD FUNCTION TO FREEZE CURRENT READINGS
- ▲ AUTO POWER OFF IN 15 OR 20 MINS INACTIVITY TO SAVE POWER
- ▲ TRIPOD MOUNTABLE RECEPTACLE

	8908	8918
Wind speed range	0.5~44.7M/H, 60~3937FT/M, 0.4~38.8KNT, 1.1~20.0M/S, 0.7~72.0KMH, 1~8BF	
Wind speed accuracy	+/-5% of rdg. or last significant digit(whichever is greater)	
Air temp. range	-15~50.0°C	-15~50.0°C
Air temp. resolution	0.1°C/°F	0.1°C/°F
Air temp. accuracy	+/-1°C	+/-1°C
Air RH% range	N/A	5%RH~95%RH
Air RH% resolution	N/A	0.1%RH
Air RH% accuracy	N/A	+/-3%RH(at 25°C, 10~90%RH, others +/-5%RH)
Wind speed response time	averaging every 2 seconds	
Temp. response time	60 seconds (typical)	
Air RH% response time	N/A	60 seconds (typical)
LCD update	every second	
Windchill display	YES	YES
Dew point temp. display	N/A	YES
LCD size	16(H)x28(W)mm	
Operating temp.	-15~50°C	
Operating RH%	Humidity < 80%	
Storage temp.	-10~50°C	
Storage RH%	Humidity < 90%	
Dimension(mm)	140x45x25 (90°folded); 235x45x25 (180°full opened)	
Weight	~90g	
Battery	CR2032 x 1pc	
Standard Package	Meter/Battery/Manual/Strap/Paper box	

Optional



REPLACEMENT MINI FAN
P/N: VP8908SP
FOR MINI ANEMOMETER 8908/ 8918
FAN SIZE: 32mm DIA.