

CENTER 220 Series Mini Clamp Meter

Low Cost/AC/DC/High Resolution



CENTER®

CENTER 220/221/222 Mini Clamp Meter

FEATURE

- Pocket Size
- Auto Ranging (221/222)
- Auto Power Off (222)
- Peak Hold Function (222)
- Data Hold Function
- Touch Zero Function (222)
- 0.1A Resolution at Full Range (222)

SPECIFICATIONS

Sampling Rate: 2 Times/sec
Jaw Opening Diameter: 25mm
Peak Hold Capture Time: 10ms
Battery: 1.5V, Size AAA Battery x 2
Dimension: 187 x 50 x 29mm
Weight: Approx. 210g



CENTER 220

Function	Range	Resolution	Accuracy
ACA	20A	0.01A	± 2%rdg + 5dgts
	200A	0.1A	
	600A	1A	

CENTER 221

Function	Range	Resolution	Accuracy
ACA	200A	0.1A	± 2%rdg + 5dgts
	600A	1A	
ACV	200V	0.1V	± 1.5%rdg + 5dgts
	600V	1V	
Ohm	200Ω	0.1Ω	± 1.9%rdg + 3dgts
🔊	Active Sound Level: ≤ 100Ω		



CENTER 222

Function	Range	Resolution	Accuracy
DCA	600A	0.1A	± 2.5%rdg + 10dgts
ACA	600A	0.1A	± 2%rdg + 5dgts
ACV	600V	0.1V	± 1.5%rdg + 5dgts
DCV	600V	0.1V	± 1%rdg + 2dgts
Ohm	1000Ω	0.1Ω	± 1%rdg + 3dgts
🔊	Active Sound Level: ≤ 100Ω		

CENTER 223 High Resolution Clamp Meter

FEATURE

- Pocket Size
- 1mA Resolution
- Peak Hold Function
- Data Hold Function
- Auto Ranging
- Auto Power Off
- Touch Zero Function
- Analog Signal Output Function



SPECIFICATIONS

Sampling Rate: 2 Times/sec
Jaw Opening Diameter: 12.5mm
Battery: 1.5V, Size AAA Battery x 2
Dimension: 202 x 50 x 29mm
Weight: Approx. 210g

Function	Range	Resolution	Accuracy
DCA	10A/100A	1mA/10mA	± 2.5%rdg + 10dgts
ACA	10A/100A	1mA/10mA	± 2%rdg + 10dgts
ACV	600V	0.1V	± 1.5%rdg + 5dgts
DCV	600V	0.1V	± 1%rdg + 2dgts
Ohm	10KΩ	1Ω	± 1%rdg + 3dgts
🔊	Active Sound Level: ≤ 100Ω		
Analog Output: 10mV/Amp ; Frequency Response: 20KHz			

CENTER®
CENTER TECHNOLOGY CORP.

4/F., NO.415, Jung-Jeng Rd., 238 Shu-Lin, Taipei, Taiwan
 TEL: 886-2-26763926 E-Mail: center@centertek.com
 FAX: 886-2-26763925 http://www.centertek.com

Distributed by: