

Detection of R-134a, R-410A, R-407C, R22, R32, R1234yf, R507A, R404A...  
freon gas and SF6 gas

## FEATURES



Refrigerant Leakage Detector is the perfect tool for maintaining the air-condition or a cooling system with compressor and Refrigerant. This unit uses a newly developed infrared gas sensor which is extremely sensitive to variety of general used Refrigerant.



DC 5V Jack

## SPECIFICATIONS

- Microprocessor Control with advanced digital signal processing.
- Multi color visual display.
- High-median-Low leak sensitivity selector.
- Low battery indication.
- Infrared gas sensor.
- Detection of R-134a, R-410A, R-407C, R22, R32, R1234yf, R507A, R404A... Freon gas and SF6 gas.
- Carrying case included.
- 15.5" (40 CM) flexible stainless probe.
- Ambient concentration reset.
- Peak function – hold the peak signal when LED can not be seen.
- Mute function.
- Auto-matic zero and background compensation.
- Warm-up Time: 45 Seconds.
- Operating Temperature: 0 to 40°C(32 to 104°F)
- Dimension: 254 x 71 x 54 mm
- Weight: 416g(with batteries)
- Power Usage: 3.7vdc rechargeable lithium Batteries.
- Battery Life: Appro. 7hrs
- AC Adapter: @5V 1A



Certificate No. 49Q13377

\* The specifications and other information in this catalogue are subject to change without prior notice.

# CENTER®

## CENTER TECHNOLOGY CORP.

4F, No.415, Jung-Jeng Road, Shu-Lin Dist.,  
New Taipei City 238, Taiwan  
TEL: 886-2-26763926 E-Mail : center@centertek.com  
FAX: 886-2-26763925 http : //www.centertek.com

Distributed by: