



COATING THICKNESS GAUGE GUN-TYPE MODEL: 115



FEATURES:

- Ferrous and non-ferrous materials measuring
- Data logging function capacity up to 255 samples
- Warning beeper triggers by Hi/Lo limit settings
- On-line display selects AVG, MAX, MIN and MAX-MIN.
- Fast one point calibration for frequent measuring thickness use.
- 2 points calibration for normal use.
- Auto-power off to save battery life
- μm/mils user-selective.
- Display Back-Light feature.

Note: Calibration material zero and 39.6 mils (1006μm) before use.

SPECIFICATIONS

- Display: 3½ digit liquid crystal display (LCD) with a maximum reading of 1999.
- Low battery indication: The "🔋" is displayed when the battery voltage drops below the operating level.
- Operating environment: 0°C to 40°C at <90% R.H. Without strong magnetic field.
- Storage temperature: -20°C to 60°C, 0 to 80% R.H. with battery removed from meter.
- Accuracy: Stated accuracy at 23°C±5°C, <75% R.H.
- Auto power off: 15 seconds.
- Dimensions: 148mm(H) x 105mm(W) x 42mm(D).

TECHNICAL DATA

- Range: 0 to 40.0mils (0 to 1000μm)
- Resolution: 0.1mils/1μm
- Response Time: 1 second
- Accuracy: ±(4dgts) on 0 to 7.8mils
 ±(10dgts) on 0 to 199μm
 ±(3%+4dgts) on 7.9mils to 40mils
 ±(3%+10dgts) on 200μm to 1000μm

CHY FIREMATE CO., LTD.
 NO.3 SHENG-LI 1ST STREET, HSIN-TIEN VILLAGE,
 JEN-TE HSIANG, TAINAN HSIEN, TAIWAN R.O.C.
 TEL: 886-6-2794811 FAX: 886-6-2700227
 E-Mail: chy@ksts.seed.net.tw Ver.12. 102208

Customer Approved By:	Prepared By:
	Bruce Hsieh Engineer Manager CHY