

Dual Input Differential Manometer

Model: 886

Model: 886U (USB+Adapter)

Model: 885W (Wireless)

Model: 886UW
(USB+Adapter+Wireless)



For Model: 886U/886UW



Features:

- USB Port provides excellent user interface (886U/886UW)
- DC 12V adapter (886U/886UW)
- Wireless two ways transmission (886W/886UW)
- Most robust differential pressure meter.
- 4 switchable units: InWC, mmWC, mBar, psi
- Rubber-boot protection for tough applications
- Dual Display and Dual input
- Main Display: P1
- Second Display: P1-P2, P2

Applications:

- HVAC system troubleshooting
- Gas pressure measurement

Specifications:

Accuracy: Stated accuracy at 23°C±5°C, <75% R.H.
Operating environment: 0°C to 50°C, (32°F to 122°F) ambient.
Compatible Media: Dry, non-corrosive gases.
Battery Life: 200 hours with low battery indication on display.
Units of Measure: InWC, mmWC, mBar, psi.
Pressure Ports: tube connectors for 8mm I.D. flexible tubing.
Battery: 1.5Vx4pcs AAA size.
Dimensions: 171mm(H) x 83mm(W) x 40mm(D).
Weight: approx. 230g including batteries

Measurement range:

InWC: 0.00 to ±60.00
mmWC: 0.0 to ±1500.0
mBar: 0.00 to ±150.00
psi: 0.000 ± 2.0000
Accuracy: ±1.5% FS

(886U/886UW)

Accessories: USB cable.
12VDC Adaptor.(Option)

(886W/886UW)

WIRELESS Features:

Frequency range: 910~920MHz.
Low current consumption less than 1mA.
The transmitting distance can reach 25M without magnetic interference.



CHY FIREMATE CO., LTD.
NO.3 SHENG-LI 1ST STREET, HSIN-TIEN VILLAGE,
JEN-TE HSIANG, TAINAN HSIEN, TAIWAN R.O.C.

Tel : 886-6-2794811
Fax : 886-6-2700227
E-Mail : chy@ksts.seed.net.tw