

# Digital ACA/DCA Clamp Meter



- 3999 counts, bar graph display
- Auto ranging
- Auto power off
- Overload protections
- Safety input jacks
- Safety test leads
- Safety: IEC1010-1, IEC1010-2-032, CAT III 1000V, CE approved.
- Jaw opening capability: 57mm conductor, 70 x 18mm bus bar.
- Dimensions: 277mm(H) x 102mm(W) x 49mm (D)
- Weight: Approx. 540g

## SPECIFICATIONS (TRUE RMS)

- DC Current: 400A, 1000A  $\pm 1.5\%$  (2606)  
400A, 2000A  $\pm 1.5\%$  (2608)
- AC Current: 400A, 1000A  $\pm 1.5\%$  (50 - 400Hz) (2606)  
(TRUE RMS) 400A, 1500A  $\pm 1.5\%$  (50 - 400Hz) (2608)
- DC Volts: 400mV, 4V, 40V, 400V, 1000V  $\pm 0.5\%$
- AC Volts (TRUE RMS): 400mV, 4V, 40V, 400V, 750V  $\pm 1.5\%$  (50 - 500Hz)
- Resistance: 400 $\Omega$ , 4k $\Omega$ , 40k $\Omega$ , 400k $\Omega$ , 4M $\Omega$ , 40M $\Omega$   $\pm 1\%$
- Capacitance: 4nF, 40nF, 400nF, 4 $\mu$ F, 40 $\mu$ F  $\pm 1.5\%$
- Frequency: 100Hz, 1kHz, 10kHz, 100kHz, 400kHz  $\pm 0.1\%$
- Diode Test
- Continuity Test
- DATA Hold
- MAX/MIN Hold
- PEAK Hold
- ZERO ( $\Delta$  Relative)
- Resolution: 0.1A, 100 $\mu$ V, 0.1 $\Omega$ , 1p, 0.01Hz