

**Features:**

- 1) High accuracy  $\pm 0.05^\circ @ (0^\circ \pm 5^\circ)$ , high resolution  $0.1^\circ$
- 2) User friendly LCD display angle
- 3) Rechargeable
- 4) Audible alarming at  $0^\circ, 45^\circ, 90^\circ$
- 5) Fast user calibration
- 6) Laser marking (for specify model)
- 7)  $360^\circ$  measuring
- 8) Tilt direction LCD icon

**specification**

Model:	AS13-L	AS30-L	AS30-LC	AS60-L	AS60-LC
Length (cm):	13	30		60	
Accuracy:	$0.05^\circ @ 0^\circ \pm 5^\circ, 0.1^\circ @ 90^\circ \pm 5^\circ, \text{other } 0.3^\circ$				
Measuring range:	$4 \times 90^\circ$				
Resolution:	$0.1^\circ$				
Laser:	No	No	Cross 5mW	No	Cross 5mW
Laser Accuracy:	No	No	$0.5\text{mm/m}$	No	$0.5\text{mm/m}$
Response time:	<0.3s				
Audio sound:	60dB @ 30cm				
Maximum Temperature Drift:	$0.04^\circ/\text{C}$				
Operating temperature:	0 to $50^\circ\text{C}$				
Storage temperature:	10 to $60^\circ\text{C}$				
Battery:	3.7V Li-Ion Rechargeable Battery (Included)				
Power Consumption:	Standby: 200uA, Operation: 5mA.				
Standby Battery Life:	2000 hours				
Operating Battery Life:	200 hours				
Size(cm)	14.5x5x2.5	32x5x2.5	32x5x2.5	61.5x5x2.5	61.5x5x2.5