

Jtech AS60-LC

Features:

- 1) High accuracy $\pm 0.05^\circ @ (0^\circ \pm 5^\circ)$, high resolution 0.1°
- 2) User friendly LCD display angle
- 3) Rechargeable
- 4) Audible alarming at 0° , 45° , 90°
- 5) Fast user calibration
- 6) Laser marking (for specify model)
- 7) 360° measuring
- 8) Tilt direction LCD icon

specification

Model:	AS13-L	AS30-L	AS30-LC	AS60-L	AS60-LC
Length (cm):	13	30		60	
Accuracy:	0.05°@0°+/-5°, 0.1°@90°+/-5°, other 0.3°				
Measuring range:	4X90°				
Resolution:	0.1°				
Laser:	No	No	Cross 5 mW	No	Cross 5mW
Laser Accuracy:	No	No	0.5mm/m	No	0.5mm/m
Response time:	<0.3s				
Audio sound:	60dB @ 30cm				
Maximum Temperature Drift:	0.04°/°C				
Operating temperature:	0 to 50°C				
Storage temperature:	10 to 60°C				
Battery:	3.7V Li-Ion Rechargeable Battery (Included)				
Power Consumption:	Standby: 200uA, Operation: 5mA.				
Standby Battery Life:	2000 hours				
Operating Battery Life:	200 hours				
Size(cm)	14.5x5x2.5	32x5x2.5	32x5x2.5	61.5x5x2.5	61.5x5x2.5
weight(g)	121	200	212	352	363
Accessories	USB charger, manual, pouch				