# **JTECH TTL-90**

### Features:

- 1) High accuracy  $\pm (0.05^{\circ} + 1\%)$ , high resolution 0.01°
- 2) Laser Alignment
- 3) Dual and Single axis with user friendly LCD display angle
- 4) Rechargeable
- 5) V Shape metal case for easy to fit at the corner or pipe.
- 6) Magnetic base
- 7) Audible alarming at settable angle range

## **Specifications**

Accuracy: Measuring range: **Resolution:** Response time: Laser Beam: Audio sound: **Operating temperature:** Storage temperature: **User Interface:** Supply Power: Charger port: **Power Consumption: Standby Battery Life: Operating Battery Life:** Dimensions (in mm): Magnetic Base:

 $\pm (0.05^{\circ} + 1\%)$ Single axis: 360°, Dual axis: ±40° 0.01° <0.4 second Class 2, 635nm red laser, < 1mW 60dB @ 30cm 0 to 50°C -10 to 60°C Mono-color LCD with backlight Rechargeable Li-Ion Battery, 3.7Volt. 5V 500mA Mini type-B USB port Standby: 200uA, Operation: 20mA. 2000 hours 40 hours 93(L) x 66(W) x 28(H) affix at the bottom and back

## Application

-Interior decoration -Construction area -Plumbing -Floors & Stairs -Woodwork

## Including:

pcs TLL90 Protractor
pcs Charger
pcs USB cable (Charging only Not for PC communication)
pcs screw nut