

POWER ANALYZER

Model : DW-6090

ISO-9001, CE, IEC1010



- † Multi-functions : W A T T , V A , W h r , P F (Power factor) , A C V , A C A , D C V , D C A , H z , o h m .
- * True AC power(Watt) & apparent power (V A) measurement.
- * True rms display for ACV, ACA.
- * Supper large LCD, display the Watt, Power factor, Voltage & Current value at the same time.
- † Accept inductive clamp or C1 input.
- * Peak hold & data hold function.
- * Hi, low alarm setting, RS-232/USB



Lutron

LUTRON ELECTRONIC

The Art of Measurement

Bench type

POWER ANALYZER

Model : DW-6090

FEATURES

- * Multi-functions : WATT, VA, Whr, PF (Power factor), ACV, ACA, DCV, DCA, Hz, ohm.
- * True AC power(Watt) & apparent power (VA) measurement.
- * True rms display for ACV, ACA.
- * Super large LCD, easy to read-out, display the Watt, Power factor, Voltage & Current value at the same time.
- * Accept different kinds current input signal as direct input, inductive clamp probe or CT (current transformer).
- * Auto range.
- * Built-in peak hold & data hold function.
- * Watt & VA measurement with Hi, low alarm setting capability.
- * RS-232 output interface.
- * Exclusive custom exclusive design LSI circuit, provides high accuracy, reliability and durability.
- * Built-in over input indication.
- * Power supply by batteries or AC to DC adapter.
- * Built-in low battery indicator .
- * Durable bench type housing plastic case with carrying handle.

GENERAL SPECIFICATIONS

Display	* 93 mm x 52 mm large LCD (Liquid Crystal Display) display. * Multi-display unit, show Volt, Ampere, Watt, Power factor or Hz at same time.
Measurement	WATT, VA, Whr., Power factor, ACV, ACA, DCV, DCA, Hz, ohm.
Zero Adjustment	<i>Watt :</i> Watt : External adjustment by push button. <i>DCV, ACV, DCA, ACA :</i> Automatic adjustment.
Polarity	Automatic switching, "-" indicates reverse polarity.
Current input mode	Direct input, inductive clamp probe or CT.
Over input Indication	Indication of " - - - - " or " - - - - ."
Data Output	RS232 serial interface.
Sampling Time	<i>W, VA, ACA, ACV, PF, Hz :</i> Approx. 1.5 Sec. <i>DCV, DCA, OHM :</i> Approx. 1 Sec.
Operating Temp.	0 to 50 °C (32 to 122 °F).
Operating Humidity	Less than 80 % R.H..
Power Supply	<i>Battery power :</i> DC 9V, 1.5 V AA (UM-3) battery x 6 PCs. <i>AC power :</i> AC to DC 9V adapter (500 mA), optional.
Power Consumption	<i>Battery power :</i> Approx. DC 30 mA
Dimension	280 x 210 x 90 mm (11.0 x 8.3 x 3.5 inch).
Weight	Approx. 1.6 Kg (3.52 LB).
Standard	Test lead (red & black)..... 1 pair.
Accessories	Instruction Manual..... 1 PC.

ELECTRICAL SPECIFICATIONS (23± 5 °C)

OHMS		
Range	Resolution	Accuracy
9,999 ohm	1 ohm	± (1 % + 1d)
19,99 K ohm	10 ohm	
* Auto range.		
* Overload protection " Max. AC/DC 300 V.		

Watt (AC, true power), current mode from direct input		
Range	Resolution	Accuracy
0.1 to 99.9 Watt	0.1 Watt	± (1.5% + 5 d)
100 to 6,000 Watt	1 Watt	
* Accuracy are specified under the following conditions :		
a) AC input current is 0.4 ACA & 10 ACA.		
b) AC input voltage is within 110 V± 15 % and 220V± 15%.		
c) ACA, ACV input signal is sine wave, 50/60 Hz.		
d) Power factor 0.8.		
* ACA, ACV frequency response is from 40 to 400 Hz.		
* Max. volt & current input signal value :		
Volt input : Max. AC 600V, Current input : Max. AC 10 A		

Watt (AC, true power), current input cooperate with inductive probe or CT		
Range	Resolution	Accuracy
9,999 Watt	1 Watt	± (1.5% + 5 d)
99.99 KW	0.01 KW	
999.9 KW	0.1 KW	
* Accuracy will be same as the above " Direct Current Input Mode " but plus the accuracy value of Current Transformer (CT) or the accuracy value of Inductive Current Probe.		
* Input current should obey :		
Inductive Probe - 20 ACA.		
CT 100/5 A - 8 ACA.		
CT 1000/5 A - 80 ACA.		

VA (AC, Apparent Power) current mode from direct input		
Range	Resolution	Accuracy
99.99 VA	0.01 VA	± (2 % + 2d)
999.9 VA	0.1 VA	
9,999 VA	1 VA	
* Accuracy are specified under the following conditions :		
a) AC input current is 0.4 ACA & 10 ACA.		
b) AC input voltage is within 110 V 15 % and 220V 15%.		
c) ACA, ACV input signal is sine wave, 50/60 Hz.		
* ACA, ACV frequency response is from 40 to 400 Hz.		

POWER FACTOR current mode from direct input only		
Range	Resolution	Accuracy
0.01 to 1.00	0.01	± (1.5% + 2 d)
* Accuracy are specified under the following conditions :		
a) AC input current is 0.4 ACA & 10 ACA.		
b) AC input voltage is within 110 V 15 % and 220V 15%.		
c) ACA, ACV input signal is sine wave, 50/60 Hz.		
* Max. volt & current input value :		
Volt input : AC 600V, Current input : AC 10A		

Hz		
Range	Resolution	Accuracy
10.0 Hz to 99.9 Hz.	0.1 Hz	± (1 % + 1d)
100 Hz to 999 Hz.	1 Hz	
* Auto range.		
* Frequency signal input voltage level should > 6V & 600 V.		

AC VOLTAGE (true rms), DC VOLTAGE		
Range	Resolution	Accuracy
0.1 V to 299.9 V	0.1 V	DCV : ± (1 % + 1d)
300 V to 600 V	1 V	
		ACV (10 V) : ± (1 % + 7d)
		ACV (11 V to 100 V) : ± (1 % + 5d)
		ACV (Others) : ± (1 % + 1d)
* Auto range.		
* Max. input voltage : AC 600 V, DC 600 V.		
* ACV accuracy is test under input signal is sine wave, 50/60 Hz.		
* ACV frequency response is from 40 to 400 Hz.		
* ACV is true rms.		

AC CURRENT (true rms), DC CURRENT current mode from direct input		
Range	Resolution	Accuracy
0.01 A to 10.00 A	10 mA	ACA : ± 1%+3d) DCA : ± 1%+1d)
* Max. input current : AC 10 A, DC 10 A.		
* ACA accuracy is test under input signal is sine wave, 50/60 Hz.		
* ACA frequency response is from 40 to 400 Hz.		
* ACA is true rms.		

AC CURRENT (true rms), DC CURRENT current mode from inductive probe		
Range	Resolution	Accuracy
1000 A	1 A	
* Accuracy : Meter voltage range accuracy plus Inductive Probe's accuracy.		
* ACA is true rms.		

AC CURRENT current mode from CT (current transformer)		
Range	Resolution	Accuracy
CT 100/5A, 0.1 - 200.0 A	0.1 A	
CT 1000/5A, 1 - 2000 A	1 A	
* Accuracy : Meter current range accuracy plus CT (current transformer) accuracy.		
* ACA is true rms.		

Watt Hour current mode from direct input		
Range	Resolution	Accuracy
0.001 Whr to 9,999 Whr	0.001 Whr	
10.00 Whr to 99.99 Whr	0.01 Whr	
100.0 Whr to 999.9 Whr	0.1 Whr	
1000 Whr to 9999 Whr	1 Whr	
10 K Whr to 99.99 K Whr	10 Whr	
100 K Whr to 999.9 K Whr	100 Whr	
1000 K Whr to 9999 K Whr	1 K Whr	
* When Watt Hour value over 9999 K Whr, the Display value will reset to 0000 K Whr, then count up again.		
* Accuracy & other specification requirement same as " Watt " range exactly		

* Appearance and specifications listed in this brochure are subject to change without notice.