

UNI-T

UT118 SERIES
Pen Type Digital Multimeters
 UT118A / UT118B



EN 61010-1
 EN 61010-2-033
 EN 61010-031
 EN 61326-1



■ UT118A



■ UT118B

SPECIFICATIONS



Specifications	Range		Best Accuracy	
Model	SCAN Mode	AUTO Mode	UT118A	UT118B
DC Voltage(V)	3V/30V/300V	3V/30V/300V	±(1%+3)	±(1%+3)
AC Voltage(V)	3V/30V/300V	3V/30V/300V	±(1%+4)	±(1%+4)
Resistance(Ω)	300 Ω /3k Ω /30k Ω / 300k Ω /3M Ω	300 Ω /3k Ω /30k Ω / 300k Ω /3M Ω /30M Ω	±(1%+3)	±(1%+3)
Capacitance (F)	3nF/30nF/300nF/ 3 μ F/30 μ F/300 μ F	3nF/30nF/300nF/3 μ F/ 30 μ F/300 μ F/3mF	±(3%+5)	±(3%+5)
Features				
Display Count			3000	3000
Auto Range			✓	✓
EF Function			✓	✓
Diode			✓	✓
Auto Power Off	Around 10 Minutes		✓	✓
Continuity Buzzer			✓	✓
Low Battery Indication			✓	✓
Data Hold			✓	✓
MAX Mode			✓	✓
MIN Mode			✓	✓
LCD Backlight			✓	✓
Penlight			✓	✓
Input Impedance for DCV	≥ 10M Ω		✓	✓

GENERAL CHARACTERISTICS

Power	3V Li-MnO ₂ Coin Cell Battery
LCD Size	28mm×14mm
Product Color	Red and Grey
Product Net Weight	90 g
Product Size	20mm×27mm×182mm
Standard Accessories	Battery, Test Lead
Standard Individual Packing	Blister, English Manual
Standard Quantity Per Carton	80 PCs
Standard Carton Measurement	570mm×300mm×415mm (0.071 CBM Per Export Carton)
Standard Carton Gross Weight	15 Kg