

**UNI-T®**

**UT200 SERIES**  
**400-600A Digital Clamp Meters**  
 UT203 / UT204 / UT204A



Intertek

UL 61010-1  
 IEC 61010-2-032  
 EN 61010-1  
 EN 61010-2-033  
 EN 61010-2-032  
 EN 61326-1



■ **UT203**



■ **UT204**



■ **UT204A**

**SPECIFICATIONS**



Specifications	Range	Best Accuracy		
		UT203	UT204	UT204A
Model		UT203	UT204	UT204A
AC Current(A)	40A/400A 40A/600A	±(2.5%+5)	±(2.5%+5)	±(2.5%+5)
DC Current(A)	40A/400A 40A/600A	±(2%+3)	±(2%+3)	±(2.5%+5)
AC Voltage(V)	4V/40V/400V/600V	±(1%+5)	±(1%+5)	±(1%+5)
DC Voltage(V)	400mV/4V/40V/400V/600V	±(0.8%+1)	±(0.8%+1)	±(0.8%+1)
Resistance(Ω)	400Ω/4kΩ/40kΩ/400kΩ/ 4MΩ/40MΩ	±(1%+2)	±(1%+2)	±(1%+2)
Capacitance (F)	4nF/40nF/400nF/4μF/40μF /100μF			±(4%+3)
Frequency (Hz)	10Hz~1MHz	±(0.1%+3)	±(0.1%+3)	
	10Hz ~ 10MHz			±(0.5%+3)
	10MHz			Reference only
Temperature (°C)	-40 °C~1000°C			±(2.5%+3)
<b>Features</b>				
Display Count		4000	4000	4000
Auto Range		✓	✓	✓
Jaw Capacity		28mm	28mm	28mm
True RMS			✓	
Duty Cycle	0.1%~99.9%	✓	✓	
Diode		✓	✓	✓
Auto Power Off		✓	✓	✓
Continuity Buzzer		✓	✓	✓
Low Battery Indication		✓	✓	✓
Data Hold		✓	✓	✓
Relative Mode		✓	✓	
Max Mode				✓
Setup		✓	✓	✓
Input Impedance for DCV	Around 10MΩ	✓	✓	✓

**GENERAL CHARACTERISTICS**

Power	9V Battery(6F22)
LCD Size	35.6mm × 18mm
Product Color	Red and Grey
Product Net Weight	260 g
Product Size	208mm × 76mm × 30 mm
Standard Accessories	<b>UT203/UT204</b> -Battery, Test Lead
Standard Individual Packing	<b>UT204A</b> -Battery, Test Lead, Point Contact Temperature Probe
Standard Quantity Per Carton	Gift Box, Carrying Bag, English Manual
Standard Carton Measurement	48 PCs
Standard Carton Measurement	503mm × 485mm × 295mm (0.10 CBM Per Standard Carton)
Standard Carton Gross Weight	30 Kg