

UNI-T

UT210 SERIES
200A Mini Clamp Meters
 UT210A / UT210B / UT210C



Intertek

UL 61010-1
 IEC 61010-2-032
 EN 61010-1
 EN 61010-2-033
 EN 61010-2-032
 EN 61326-1

NEW



■ UT210A



■ UT210B



■ UT210C

SPECIFICATIONS



Specifications	Range	Best Accuracy		
		UT210A	UT210B	UT210C
Model		UT210A	UT210B	UT210C
AC Current (A)	2A/20A/100A	±(1.0%+9)	±(1.0%+9)	±(2%+5)
DC Current (A)	2A/20A/100A			±(2%+3)
AC Voltage(V)	2V/20V/200V/600V			±(1.0%+3)
DC Voltage(V)	200mV/2V/20V/200V/600V			±(0.7%+3)
Resistance(Ω)	200Ω/2kΩ/20kΩ/200kΩ/2MΩ/20MΩ			±(1.0%+2)
Capacitance (F)	9.999nF/99.99nF/999.9nF/9.999µF/99.99µF/999.9µF/9.999mF/19.99mF			±(4%+5)
Features				
Display Count		2000	2000	2000
Auto Range		✓	✓	✓
Jaw Capacity		17mm	17mm	17mm
True RMS			✓	✓
Diode	Around 3.0V			✓
V.F.C.				✓
NCV			✓	✓
Data Hold		✓	✓	✓
Zero Mode				✓
Relative Mode			✓	
LCD Backlight		✓	✓	✓
Auto Power Off	Around 15 Minutes	✓	✓	✓
Continuity Buzzer				✓
Low Battery Indication	≤2.5V	✓	✓	✓
Input Protection		✓	✓	✓
Input Impedance for DCV	≥10MΩ			✓

GENERAL CHARACTERISTICS

Power	AAA 1.5V × 2
LCD Size	39.3mm × 26.5 mm
Product Color	Red and Grey
Product Net Weight	UT210A/B -160g UT210C -170g
Product Size	UT210A/B - 155mm × 60mm × 33.5mm
	UT210C - 175mm × 60mm × 33.5mm
Standard Accessories	UT210A/B - Batteries
	UT210C - Batteries, Test Lead
Standard Individual Packing	UT210A/B - Blister, English Manual
	UT210C - Blister, Carrying Bag, English Manual
Standard Quantity Per Carton	40 PCs
Standard Carton Measurement	UT210A/B - 415mm x 380mm x 280mm (0.045 CBM Per Standard Carton)
	UT210C - 550mm x 455mm x 335mm (0.084 CBM Per Standard Carton)
Standard Carton Gross Weight	UT210A/B - 11kg UT210C - 15kg