

UNI-T®

UT390 SERIES
Laser Distance Meters
 UT391A / UT392 / UT393



EN 61326-1
 EN 60825-1

NEW



■ **UT391A**



■ **UT392**



■ **UT393**

SPECIFICATIONS

| Specifications | | | |
|--------------------------------------------|---------------------|---------------------------------|---------------------|
| Model | UT391A | UT392 | UT393 |
| Accuracy (m) | ±1.5mm | ±1.5mm | ±1.5mm |
| Measuring Distance (m) | 0.05~70m | 0.05~80m | 0.05~100m |
| Unit | m/in/ft | m/in/ft | m/in/ft |
| Laser Class | 635nm,<1mw,class II | 635nm,<1mw,class II | 635nm,<1mw,class II |
| Features | | | |
| Continuous Measurement | | ✓ | |
| Multiple Lines Display | | 4 Lines | |
| Selectable Reference | | ✓ (Top,Bottom,Middle,Extension) | |
| MAX/MIN | | ✓ | |
| Add/Subtract | | ✓ | |
| Area/Volumn/Pythagoras Theorem Calculation | | ✓ | |
| Data Storage | 20 | 20 | 50 |
| Buzzer Indication | | ✓ | |
| Display Backlight | | ✓ | |
| Error Indicate | | ✓ | |
| Tripod | | ✓ | |
| Laser Power Level Indication | | ✓ | |

GENERAL CHARACTERISTICS

| | |
|------------------------------|---------------------------------------------------------------------|
| Power | AAA 2 × 1.5V |
| Product Color | Red and Grey |
| Product Net Weight | 175g (Battery not included) |
| Product Size | 126mm × 54mm × 29mm |
| Standard Accessories | Batteries, Carrying Bag |
| Standard Individual Packing | UT391A/UT392 -Clampshell, UT393 -Giftbox, User Manual |
| Standard Quantity Per Carton | UT391A/UT392 -48 PCs, UT393 -40 PCs |
| Standard Carton Measurement | 610mm × 385mm × 485mm |
| Standard Carton Gross Weight | UT391A/UT392 -13.5 Kg, UT393 -20 Kg |