

UNI-T®

UT390 SERIES
Laser Distance Meters
 UT391A / UT392 / UT393



EN 61326-1
 EN 60825-1

NEW



■ **UT391A**



■ **UT392**



■ **UT393**

SPECIFICATIONS

Specifications			
Model	UT391A	UT392	UT393
Accuracy (m)	±1.5mm	±1.5mm	±1.5mm
Measuring Distance (m)	0.05~70m	0.05~80m	0.05~100m
Unit	m/in/ft	m/in/ft	m/in/ft
Laser Class	635nm,<1mw,class II	635nm,<1mw,class II	635nm,<1mw,class II
Features			
Continuous Measurement		✓	
Multiple Lines Display		4 Lines	
Selectable Reference		✓ (Top,Bottom,Middle,Extension)	
MAX/MIN		✓	
Add/Subtract		✓	
Area/Volumn/Pythagoras Theorem Calculation		✓	
Data Storage	20	20	50
Buzzer Indication		✓	
Display Backlight		✓	
Error Indicate		✓	
Tripod		✓	
Laser Power Level Indication		✓	

GENERAL CHARACTERISTICS

Power	AAA 2 × 1.5V
Product Color	Red and Grey
Product Net Weight	175g (Battery not included)
Product Size	126mm × 54mm × 29mm
Standard Accessories	Batteries, Carrying Bag
Standard Individual Packing	UT391A/UT392 -Clampshell, UT393 -Giftbox, User Manual
Standard Quantity Per Carton	UT391A/UT392 -48 PCs, UT393 -40 PCs
Standard Carton Measurement	610mm × 385mm × 485mm
Standard Carton Gross Weight	UT391A/UT392 -13.5 Kg, UT393 -20 Kg