

NEW



EN61326-1
EN60825-1



■ UT396A



■ UT396B

SPECIFICATIONS

Specifications	UT396A	UT396B
Model	UT396A	UT396B
Accuracy	$\pm(2.0\text{mm}+d*5/100000)$, 'd' is actual distance	
Range	0.05~80m	0.05~120m
Minimum unit	1mm	1mm
Display units	m/in/ft	m/in/ft
Laser	635nm, <1mW, Class 2 (II)	635nm, <1mW, Class 2 (II)
FEATURES		
Camera	2MP	2MP
Continuous measurement	✓	✓
Area/volume calculation	✓	✓
Pythagorean	✓	✓
Distance add/subtract	✓	✓
Area add/subtract	✓	✓
Volume add/subtract	✓	✓
MAX/MIN	✓	✓
Triangle height/angle/area	✓	✓
Inclination	-90° ~ 90°	-90° ~ 90°
Delay measurement	✓	✓
Staking-out	✓	✓
Record	100	100
Electronic leveler	✓	✓
Auto power off	100-300s	100-300s
Auto laser off	20-120s	20-120s
USB connector	✓	✓

GENERAL CHARACTERISTICS

Power	1.2V 800mAh AAA NI-MH x 3 Batteries
Product Color	Red and Gray
Product Net Weight	84g
Product Size	126mm x 56mm x 28mm
Standard Accessories	Hanging cord, USB interface cable, reflector
Standard Individual Packaging	Gift box, carrying bag, manual, rechargeable battery
Standard Quantity Per Carton	60pcs
Standard Carton Measurement	520mm x 470mm x 345mm
Standard Carton Gross Weight	14.6 kg